

# Bagging System

Innovating since 1977

IPA offers rugged & reliable bagging machine to suit every kind of material & industry. These are custom-built to meet any industry's requirement offering smooth and reliable operations. IPA, with over 43 years of experience and expertise, manufactures machines that are built for reliability and accuracy.

### **Specifications**

Type Direct Bagging, Pre-weigh and dump, jumbo bagging

MaterialFine powder up to 50mm sizeFeederBelt/Vibrating tray/gateMeasurementHigh Precision LoadcellBag ClampingPneumatic / Manual

Capacity 5kg, 10kg, 20kg, 25kg, 50kg, 100kg & jumbo bag

Mounting Wall-mounting
Input Power Supply 230 V, 50Hz
Controller BST106-B66[A]
Bag Clamping Manual
Accuracy 0.15% of FS
Compressed Air reqd 6Kg/sqcm
Display Touchscreen
Speed of Bagging Up to 12bags/min
Additional Attachment Slat Conveyor
Sealing Conveyor



## **Technical Specifications**

#### **Executing Standard**

• Accuracy Grade: III.

#### **Structure Configurations**

• 7"/10.2" Ultralight and ultrathin TFT touchscreen with embedded weighing/control module.

#### **Display Operation**

- 16-bit Color screen with 800×480[7"] or 1024×600[10.2"] pixel and LED backlight.
- Graphic display interface and touch operation.

#### **Loadcell Interface**

- Connection Quantity: 8 Loadcells (350Ω).
- Excitation Voltage/Max. Current: DC5V, 120mA.
- Signal Input Range: 0~12.5mV.
- Output Sensitivity of Loadcell: 1.0~2.5mV/V.
- 24-bit ∑- ADC with internal resolution 1/1,000,000.
- Sampling Frequency: 800Hz.
- Special anti-vibration digital filtering algorithm.

#### **Switch Analog Signal Interface**

- 9 Definable Normally Open Switch Inputs [DI].
- 18 Definable Normally Open Transistor Switch Outputs [DO]: DC24V, 1A.
- 2 Definable Analog Signal Output [AO]: 0~10V/Max.50mA, Non-linearity: 0.05%FS.

#### **Digital Communication Interface**

• COM1[RS232]&COM2[RS485] for connecting Host IPC/PLC and LED Remote Display.





## IPA Pvt. Ltd.

472/B2, 12th Cross, IV Phase, Peenya Industrial Area, Bangalore - 560 058 Ph: 2836 0253 / 2836 2851

Ph: 2836 0253 / 2836 28 Email: sales@ipaindia.com





An ISO 9001 Certified Company